


SYSTEM 40® ROLLER SYSTEM WITH FREE LINK COUPLING BRACKET SET




SYSTEM 40® ROLLER FREE LINK


- Designed and manufactured in the UK, all Louvolite systems are 10 year life cycle tested to ensure long lasting performance.
- System 40® Free Link coupling brackets set joins two sets of blinds together allowing fully independent operation, whilst sharing a common centre support bracket.
- Useful when covering large areas of glass as openings with different drops can be covered using a shared intermediate bracket.
- Manufactured using high quality engineering grade polymer.
- For blinds up to 2.5m wide, with a 9lb maximum holding weight. Achieve widths of up to 3.2m using the 40mm heavy duty tube R8025-HD.
- Motorise with Louvolite One Touch lithium rechargeable series using a 40mm tube: R2110 DC, R2115 DC-SHORT, R2120 DC, R2125 DCM, R2130 DC, R2135 DCM or hard wired R2150 AC, R2155 ACM.

FREE LINK ROLLER SYSTEM

Free Link Two Equal Blinds



Free Link Two Unequal Blinds



FREE LINK ROLLER SYSTEM MOTORISED

SYSTEM	MOTOR	OPERATION
System 40®	1100 DC SERIES - R2110 DC	RF Remote Control/Smart Control/BT
	1100 DC-SHORT SERIES - R2115 DC - SHORT	RF Remote Control/Smart Control/BT
System 40®/45®	2000 DC SERIES - R2120 DC	RF Remote Control/Smart Control/BT
	2000 DCM SERIES - R2125 DCM	RF Remote Control/Smart Control/MATTER
	3000 DC SERIES - R2130-DC	RF Remote Control/Smart Control/BT
	3000 DCM SERIES - R2135 DCM	RF Remote Control/Smart Control/MATTER
	2000 AC SERIES - R2150 AC	RF Remote Control/Smart Control/BT
	2000 ACM SERIES - R2155 ACM	RF Remote Control/Smart Control/MATTER

LOUVOLITE SIDE CONTROL SYSTEMS MAXIMUM BLIND SIZE

SYSTEM	FABRIC GROUP	BLIND WIDTH (m) FOR BLIND DROP (m)						40HD	MAX HOLDING WEIGHT
		0.5	1.0	1.5	2.0	2.5	4.0	3.0	
System 40®	up to 200g/m sq 200 > 320g/m sq 320 > 485g/m sq	5.0	5.0	5.0	5.0	5.0		5.0	9lb blind at 6mm deflection
		3.75	3.75	3.75	3.75	3.75		3.75	
		5.0	5.0	5.0	3.55	2.7		2.1	
System 45®		6.0	6.0	6.0	6.0	6.0			12lb blind at 9mm deflection
		4.75	4.75	4.75	4.75	4.75			
		6.0	6.0	6.0	5.0	4.0			24lb blind at 6mm deflection
System 55®							4.5		
							2.80		
							1.85		

System 55® Easi Lift™ is recommended for use on all blinds over 10lbs (4.5kgs) to give optimum performance. Can also be used for 75mm (3") fascia.

Your Louvolite Distributor



CI/SIB 1976 reference by SIB Agency

(76.7) X

HARDWARE SPECIFICATION

System 40® Roller System

Our roller blinds are manufactured using the Louvolite System 40® roller blind mechanism with specifically designed grooved 40mm aluminium tubing. The specified fabrics are formed and held into the tube with locking tape. The side control units are made from glass filled Nylon 6, with an acetal sprocket and sprocket guard, and includes a locking spring.

The operating chain, No. 10 size in metal or plastic, ensures reliable performance, and improved chain location enables quick and easy on-site adjustment. The mild steel brackets are zinc plated and powder coated, suitable for top, face or side fixing.

A spring plunger end mechanism is positioned at the opposite end to the control unit, providing a more secure fit of the blind and smooth operation. The side control unit is fitted with a centre plug that ensures the mechanism operates smoothly even under extreme loads.

Colour spec: White RAL 9010, Black RAL 9011.

Performance

To ensure a positive performance, all Louvolite Roller System units are designed and manufactured in the UK using prime quality plastic materials and a dedicated steel locking spring. The sidewinders will lock into the bracket with the unique bracket securing pin for safety after installation.

10 year life cycle testing is done to ensure long lasting performance.

Operation

Using manual or motorised operation, all blinds must be compliant with the child safety elements of BS EN13120. Where children may be present, the chain must be fitted with easybreak connectors or a cord tidy.

Bottom Bar

Teardrop, made of aluminium or pvc, can be single or double wrapped in fabric or left exposed, while circular and the dual face Gemini, made of aluminium, only have the fabric formed and locked into the top part to leave the bar exposed. All fabric is formed and held into place with locking tape.

The dual face Gemini bar, smooth on one side and angular on the other, improves the ease of manufacture and use of thicker laminate fabrics.

Maintenance

All of the System 40® roller blind system components are manufactured using aluminium, treated steel and plastic. They do not present any corrosion problems in normal environments. The system has been designed for a smooth operation, together with a rigidity to prolong the window blind's working life. Manufacturing size restrictions are included in this specification brochure.

Additional Options

Cassettes are specially designed and powder coated with dedicated top fix or face fix brackets. The user has the choice between a single coloured extrusion in various colours or a fascia which incorporates the same fabric or contrasting fabric. Other options not shown are 40mm Back Bar, 40mm Hybrid Closed Cassette, 40®/45® Closed Cassette and 75mm (3") Fascia.

NOTES